

MI-setral-PU 100

High-performance grease

APPLICATION: For long-term lubrication at low and high operating temperatures.
For plain, roller and ball bearings. Especially for heavily loaded bearings, joints, slides, hinges and guiding mechanisms.

ADVANTAGES:

- * Stable to cold and hot water
- * No bleeding at operation under vibrations
- * Reliable corrosion protection
- * Reduces wear and tear
- * Good pumpability in central lubricating systems
- * High DN-value
- * Economical through high operational reliability

METHOD OF USE: As usual with greases.
Refer to recommendations of bearing manufacturers.
Do not mix with other greases.

PACKAGING:

25	kg	hobbock
180	kg	drum

ARTICLE-NO.: 0393

TECHNICAL DATA:

Colour:	brown, natural		
Base:	mineral oil		
Thickener:	Polyurea		
Consistency:	2	NLGI-grade	DIN 51818
Drop point:	> 220	°C	ISO 2176
Temperature range:	- 30 up to + 150	°C	
	short-term up to + 170	°C	
DN-factor:	500.000		

The information in this bulletin is, to our knowledge, true and accurate, but all recommendations are without guarantee, since the conditions of use are beyond our control. Setral disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

0393e / 301194