

SYN-setral-INT/250 A-series

Synthetic special greases, stable at high temperatures and aggressive atmosphere

APPLICATION: Rolling and plain bearings in rollers of circle conveyors, stove enamel ovens, waffle ovens etc.
Chemical plants, plastic industry, nuclear power plants, electronic equipment, automotive industry and for vacuum applications.

ADVANTAGES:

- * Resistant against solvents and acidic vapours
- * High wear protection and load carrying ability
- * Long re-lubrication intervals, even at high temperatures
- * Insoluble in solvents, acids
- * Economic in use
- * Non-combustible

METHOD OF USE: Clean and degrease lubrication points carefully prior to application.
For this CLEAN-setral-AN/U spray is specially suited.
IMPORTANT - Please consider the density of app. 1.9.
Apart from that please refer to recommendations of bearing manufacturers.
Do not mix with other greases and oils.

PACKAGING: 0,8 kg cartridge
1,0 kg tin (other packaging on request)

ARTICLE-NO.: 0315 0319 0350

TECHNICAL DATA:	A 2	A 1	A 00		
Colour:		white			
Density, 20 °C:		app. 1,9		g/cm ³	DIN 51757
Basis:		PFPE			
Base oil viscosity at 40°C:		510		mm ² /s	DIN 51562
Thickener:		PTFE			
Consistency:	265 – 295	310 – 340	400 – 430	mm ⁻¹	DIN ISO 2137
Consistency class:	2	1	00	NLGI-class	DIN 51818
Drop point:		non dropping			DIN ISO 2176
Flow pressure at -30°C:	600	-	-	hPa	DIN 51805
Flow pressure at -40°C:	1550	1350	-	hPa	DIN 51805
Temperature range:		- 40 bis + 250°C (short term + 300 °C)			
nD _m -factor:		250.000			

The information in this bulletin is, to our knowledge, true and accurate, but all recommendations are without guarantee, since the conditions of use are beyond our control. Setral disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

0315e / 160109

Setral Chemie GmbH
Salzsteinstrasse 4
D-82402 Seeshaupt
Telefon : +49 (0) 88 01 97 10
Telefax: +49 (0) 88 01 97 30
Email: info@setral.net

Sétral S.à.r.l.
13, rue Tannmuhle
F-67310 Romanswiller
Téléphone: +33 (0) 3 88 59 11 59
Télécopie: +33 (0) 3 88 59 11 57
Email: france@setral.net