

SYN-setral-PU 2

Synthetic polyurea grease for very low and high temperatures

APPLICATION: Rolling and plain bearings working under severe conditions like temperature, water, load, speed etc.
Bearings of electric motors, fans, conveyors, generators. Dryer sections of paper machines.

ADVANTAGES:

- * Reduces friction and wear
- * Extreme pressure properties
- * Low starting torque, even at low temperatures
- * Good corrosion protection
- * Very high oxidation stability
- * Extended lubrication intervals
- * Good shear stability

METHOD OF USE: As usual with greases.
Refer to recommendations of bearing manufacturers.

PACKAGING:

25	kg	hobbock
180	kg	drum

ARTICLE-NO.: 0310

TECHNICAL DATA:

Colour:	light yellow		
Thickener:	polyurea		
Consistency:	2	NLGI-grade	DIN 51818
Drop point:	appr. 250	°C	ISO 2176
Temperature range:	- 40 up to + 180	°C	
DN-factor:	appr. 500.000		
Four ball weld load:	4000	N	

The information in this bulletin is, to our knowledge, true and accurate, but all recommendations are without guarantee, since the conditions of use are beyond our control. Setral disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

0310e / 270301