VISCHEM® 352

SYNTHETIC MULTI-PURPOSE GREASE

Applications:

Vischem 352 is a fully synthetic multi-purpose grease formulated for use in a wide variety of applications. Vischem 352 is soft and applies easily; only a thin film is required. Vischem 352 will not wipe of, sling off, or drip off.

Typical Industrial Applications:

- Business Machines
- Gear Boxes
- Gas Meters
- Tools
- Bearings
- Control Mechanisms
- Parking Meters
- Timers
- Clocks

- Speedometers
- Potentiometers
- Instruments
- Counters
- Motors
- Appliances
- Optical Instruments
- Recorders
- Sound Equipment

Performance Benefits:

- Excellent anti-wear properties
- Will not dry out to form gum, sludge, or other deposits
- Longest possible life
- Protects against humidity and prevents rust
- Wide temperature range, -65°F to 300°F

TYPICAL PROPERTIES	TEST METHOD	Vischem 352
NLGI Grade		1
Color	Visual	Light Tan
Structure	Visual	Smooth
Penetration Worked (60 strokes) Unworked	ASTM D217 ASTM D217	330 325
Dropping Point, °C	ASTM D2265	187
Oil Separation, 24 hrs. at 100°C, %	ASTM D6184	6.0
Evaporation, 24 hrs. at 100°C, %	СТМ	0.36
Water Washout @ 38°C, %	ASTM D1264	2.1
Base Oil		Synthetic

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE IN USA



900 Centerpoint Blvd. New Castle, DE 19720 P......302-325-9880 F......302-325-0335 info@ultracheminc.com

WWW.ULTRACHEMINC.COM